

02-FEB-06  
BD-2 BELT DRESSING - SAFEGAR

Murdock Electric & Supply

PO Box 2775  
Wichita KS 67214

To Whom It May Concern:

As you requested, attached is a copy of a Material Safety Data Sheet covering (our ref. no. 800165) BD-2 BELT DRESSING - SAFEGAR.

Title III of the Superfund Amendments and Reauthorizations Act (SARA) requires chemical suppliers of mixtures and trade name products to provide information to their customers sufficient for them to comply with the requirements of Section 313.

Material Safety Data Sheets (MSDS's) have been updated to include the section 313 information.

Steve Smith  
Regulatory Manager

## MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

## IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME:  
BD-2 BELT DRESSING - SAFEGARD

PRODUCT #:  
800165

CHEMICAL NAME:  
N/A - Mixture

CAS #'S:  
N/A - Mixture

PRODUCT APPEARANCE AND ODOR:  
Amber liquid, solvent odor

CHEMICAL FAMILY:  
Petroleum Hydrocarbon

SYNONYMS:  
Belt dressing non aerosol spray

EMERGENCY TELEPHONE:  
1-908-862-9300

## COMPONENTS AND HAZARD INFORMATION

COMPONENTS:	% W/W	HAZARD DATA (TLV, ETC.):
Aliphatic Solvent CAS # 64742-47-8		TLV 300ppm
Phthalate ester of hydroabietyl alcohol CAS # 36388-36-0		n/e

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):

Health	Flammability	Reactivity
1	2	0

## TRANSPORTATION INFORMATION

## TRANSPORTATION INFORMATION:

DOT SHIPPING INFO:

AEROSOLS, Class 2.1 (Flammable Gases)

UN 1950, PG None

Note: see 49 CFR 173.306 for Limited Quantity provisions

## EMERGENCY FIRST AID

## EYE CONTACT:

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

## SKIN CONTACT:

In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

## INHALATION:

If overcome by vapor, remove from exposure and call a physician immediately.

## MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

**EMERGENCY FIRST AID**

If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

**INGESTION:**

If ingested, DO NOT induce vomiting; call a physician immediately.  
Possible aspiration hazard.

**FIRE AND EXPLOSION HAZARD INFORMATION**

FLASHPOINT (MINIMUM):  
For solvent: Combustible, 142°F TCC

AUTOIGNITION TEMPERATURE:  
>392°F

**NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION:**

Health	Flammability	Reactivity
1	2	0

The Aerosol Flammability test (per 49 CFR 173.306(i)) produced a flame extension exceeding 18 inches, thus this product is classified as Flammable per the DOT Regulations.

**HANDLING PRECAUTIONS:**

Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

**FLAMMABLE OR EXPLOSIVE LIMITS (Approximate percent by volume in air):**

Estimated values: Lower Flammable Limit N/E Upper Flammable Limit N/E

**EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES:**

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Water may be ineffective, but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect men attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Note: The inclusion of the phrase "water may be ineffective" is to indicate that although water can be used to cool and protect exposed material, water may not extinguish the fire unless used under favorable conditions by experienced fire fighters trained in fighting all types of flammable liquid fires.

**DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:**

Fumes, smoke, carbon monoxide, aldehydes and other decomposition products, in the case of incomplete combustion.

**"EMPTY" CONTAINER WARNING:**

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous.

## MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

### FIRE AND EXPLOSION HAZARD INFORMATION

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove.

All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

### HEALTH AND HAZARD INFORMATION

#### VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

#### POTENTIAL HEALTH EFFECTS (For solvent component):

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 700 ppm, attainable at elevated temperatures well above ambient) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the pulmonary system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. Minimal toxicity.

CHRONIC EFFECTS: At high oral doses, the solvent caused reversible damage to the liver and kidney (male only) of rats. These effects are not relevant to humans at occupational levels of exposure.

### PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes. FOR SOLVENT:

BOILING RANGE:  
Approximately 360°F to 419°F

VAPOR PRESSURE:  
3 mm Hg @ 100°F, approximate  
ASTM D 2897

SPECIFIC GRAVITY 60°F  
N/E

VAPOR DENSITY (AIR = 1):  
Greater than 1

MOLECULAR WEIGHT:  
Mixture, wide range

PERCENT VOLATILE BY VOLUME:  
75

pH:  
Essentially neutral

EVAPORATION RATE @ 1 ATM. AND 25°C  
(77°F):  
(n-BUTYL ACETATE = 1)

## MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

### PHYSICAL DATA

POUR, CONGEALING OR MELTING POINT: Less than 0.1  
n/e SOLUBILITY IN WATER @ 1 ATM. AND  
25°C (77°F):  
Negligible; less than 0.1%

### REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS  
Fumes, smoke, carbon monoxide, and other decomposition products, in the case of incomplete combustion.

If this product is heated to temperatures sufficient to produce smoke or fumes, the TLV-TWA of 0.1 mg/m<sup>3</sup> (as formaldehyde), for rosin core solder pyrolysis products should be observed.

#### CONDITIONS TO AVOID

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

### TOXICITY

ORAL (Acute)	N/E
DERMAL (Acute)	N/E
EYE	N/E
INHALATION (Acute)	N/E
CHRONIC, SUBCHRONIC, ETC.	N/E

Medical Conditions Aggravated by Exposure: Unknown

This product does NOT contain any ingredients identified as carcinogenic by IRAC, NTP, or OSHA.

SARA Section 313 Status: This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

### SPILL OR LEAK PROCEDURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all

## MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

---

**SPILL OR LEAK PROCEDURES**

---

windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.)  
Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

---

**PROTECTION AND PRECAUTIONS**

---

VENTILATION: (Always maintain below permissible exposure limits.)  
Use local exhaust to capture vapor, mist or fumes, if necessary.  
Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)  
Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or mist respirator type under misting conditions. Use can or cartridge; gas or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:  
Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:  
Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:  
Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS:  
Keep containers closed when not in use. Do not handle near heat, sparks, flame, or strong oxidants. DO NOT PUNCTURE OR INCINERATE CONTAINER!

PERSONAL HYGIENE:  
Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

---

PREPARED BY: Steve Smith

REGULATORY MANAGER

---

MATERIAL SAFETY DATA SHEET FOR BD-2 BELT DRESSING - SAFEGARD

TOTAL Lubricants USA, Inc.  
5 N. Stiles Street  
Linden NJ 07036

REVISION DATE  
27-JAN-06

DATE ISSUED  
02-FEB-06

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE.  
HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE  
SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE  
BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR  
IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE  
INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE  
THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA  
RELEVANT TO HIS PARTICULAR USE.