

Material Safety Data Sheet

Print date: 07/05/2005

Version: 2

Revision date: 01/21/2005

1. COMPANY AND PRODUCT IDENTIFICATION

Product code:

014240-01 02

Product name:

QUAKERCUT™ 010 ES

Supplier:

Quaker Chemical Corporation Quaker Park One 901 Hector Street Conshohocken, PA 19428

610-832-4000

E-mail: she@quakerchem.com

Emergency telephone number:

* 24 HOUR TRANSPORTATION: **CHEMTREC: 1-800-424-9300

703-527-3887 (Call collect outside of US)

* 24 HOUR EMERGENCY HEALTH & SAFETY: **QUAKER CHEMICAL CORPORATION: (800) 523-7010(

Within US only)

Outside of US call (703) 527-3887

2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

Components	Weight %	CAS No.	OSHA Ceiling Limits	OSHA TWA (final):	ACGIH Ceiling Limits	ACGIH Exposure Limits:	Vendor Exposure Limits:
Mineral Oil*	80 - 90%	8012-95-1		5mg/m³		5 mg/m³	None

^{*} May include one or more of the following CAS #: 64741-88-4, 64741-89-5, 64741-96-4, 64741-97-5, 64742-46-7, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-62-7 and 64742-65-0, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1.

3. HAZARDS IDENTIFICATION

Emergency Overview

Mild eye irritation.

May cause skin irritation and/or dermatitis. May cause irritation of respiratory tract. May be harmful if swallowed.

Principle routes of exposure:

Eyes, skin and inhalation.

Signal word:

CAUTION

Eve contact:

May cause slight irritation.

Skin contact:

Repeated or prolonged contact with base product may cause irritation leading to

various skin disorders such as dermatitis, oil acne, or foliculitis.

Inhalation:

Inhalation of vapor (generated at high temperatures only) or oil mist from this product

may cause mild irritation of the upper respiratory tract.

Page 1 of 7

Ingestion: Ingestion may cause gastrointestinal imitation, nausea, vomiting and diarrhoea.

Physico-chemical properties: No hazards resulting from material as supplied.

4. FIRST AID MEASURES

General advice: If symptoms persist, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes.

Skin contact: Rinse immediately with plenty of water for at least 15 minutes

Ingestion: If swallowed, seek medical advice immediately and show this container or label.

Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapors. If not breathing, give

artificial respiration. If breathing is difficult, give oxygen. Consult a physician.

Notes to physician: Treat symptomatically.

Medical condition

aggravated by exposure:

Dermatitis.

5. FIRE-FIGHTING MEASURES

Flash point (°C): 146 Flash point (°F): 295 Flash Point Method: COC

Flammable limits in air - upper (%): Not determined Flammable limits in air - lower (%): Not determined

Suitable extinguishing

media:

Unusual hazards:

None known

Special protective equipment for fire-fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

Use dry chemical, CO2, water spray or 'alcohol' foam.

and full protective gear.

Specific methods: Water mist may be used to cool closed containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ensure adequate ventilation.

Environmental precautions: Do not flush into surface water or sanitary sewer system.

Methods for cleaning up: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust).

7. HANDLING AND STORAGE

Handling

Technical

Provide sufficient air exchange and/or exhaust in work rooms.

measures/precautions:

SDS code: 014240-01 02 Product name: QUAKERCUT™ 010 ES Page 2 of 7

Safe handling advice:

In case of insufficient ventilation, wear suitable respiratory equipment.

Storage

Technical measures/storage

conditions:

Store at room temperature in the original container

incompatible products:

No special restrictions on storage with other products

Safe storage temperature:

40-100 °F

Shelf life:

6 months

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components	ACGIH Ceiling Limits	ACGIH Exposure Limits:	OSHA Ceiling Limits	OSHA TWA (final):	NIOSH - Pocket Guide - TWAs:	Vendor Exposure Limits:
Mineral Oil*		5 ma/m³		5mg/m³	5ma/m³	None

Engineering measures:

Ensure adequate ventilation.

Personal Protective Equipment

General:

Eye Wash and Safety Shower

Respiratory protection:

If engineering controls do not maintain airborne concentrations to a level which is

adequate to protect worker health, a certified respirator that will protect against

organic vapor must be worn.

Hand protection:

Neoprene gloves

Skin and body protection:

Usual safety precautions while handling the product will provide adequate protection

against this potential effect.

Eye protection:

Safety glasses with side-shields.

Hygiene measures:

Avoid contact with skin, eyes and clothing.



9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical state:

Liquid

Color:

Clear, Amber

Odour:

Bland, Ester-like Not determined

Vapour pressure: Vapour density:

Not determined

VOC Content Product:

1.60 lb/gal (EPA Method 24)

Solubility:

Insoluble

Evaporation rate: :Hq

Not determined

Flash point (°C):

NA

Flash point (°F):

146

Decomposition temperature:

295

Not determined

Auto-ignition temperature:

Not determined

Density @ 15.5 ° C (g/cc) : Bulk density @ 60 ° F (lb/gal): 0.866 7.23

Partition coefficient

Not determined

(n-octanol/water, log Pow):

Explosive properties:

upper limit:lower limit:

No data available

10. STABILITY AND REACTIVITY

Conditions to avoid:

None known

Materials to avoid:

Strong oxidising agents

Hazardous decomposition products:

Carbon oxides, Sulphur oxides

Stability:

Stable under recommended storage conditions.

Polymerization:

Not applicable

11. TOXICOLOGICAL INFORMATION

MINERAL OIL INFORMATION: Any product containing a substance for which OSHA has established a permissible exposure limit (PEL) is considered hazardous. OSHA has established a PEL of 5 mg/m³ for worker exposure to air borne mists of mineral oils. Therefore, the presence of mineral oils brings this product within the provisions of the OSHA Hazard Communication Standard where the PEL reaches or exceeds 5 mg/m³. Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

No toxicological information is available on the product. Data obtained on components are summarized below.

Components	NTP:	IARC:	OSHA - Select Carcinogens	NIOSH - Selected LD50s and
				LC50s
Mineral Oil*	This product does not contain any material shown to be a carcinogen by the National Toxicology Program (NTP).	This product does not contain any material shown to be a carcinogen by the International Agency for Research on Cancer (IARC).	a carcinogen by	22g/kgOral LD50Mouse 4300mg/kgOral LD50Mouse 4300mg/kgOral LD50Rat

12. ECOLOGICAL INFORMATION

Persistence and degradability:

No information available

SDS code:

014240-01 02

Product name: QUAKERCUT™ 010 ES

Mobility:

No data available

Bioaccumulation:

No data available

Ecotoxicity effects:

No data available

Aquatic toxicity:

Not Determined

13. DISPOSAL CONSIDERATIONS

Waste from residues/unused

products:

Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

Contaminated packaging:

Do not re-use empty containers

Methods for cleaning up:

Take up mechanically and collect in suitable container for disposal.

14. TRANSPORT INFORMATION

U. S. DEPARTMENT OF TRANSPORTATION:

Proper shipping name:

RQ:

Not Regulated

TDG (CANADA):

Proper shipping name:

Not Regulated

IMDG/IMO:

Proper shipping name:

Not Regulated

IATA/ICAO:

Proper shipping name:

Not Regulated

15. REGULATORY INFORMATION

CLASSIFICATION AND

LABELING

OSHA Hazard Communication

Standard:

This product is considered to be hazardous under the OSHA Hazard Communication Standard.

Canada - WHMIS Classification

Information:

This product has been classified according to the hazard criteria of the CPR and the

MSDS contains all the information required by the CPR.

Product Classification: Product Classification

Graphic(s):

None Required

SDS code:

014240-01 02

Product name: QUAKERCUT™ 010 ES

Page 5 of 7

Component Classification

Data:

Mineral Oil* - 8012-95-1

WHMIS hazard class:

1 % (English Item 1224, French Item 977)

Uncontrolled product according to WHMIS classification criteria

Canadian National Pollution

Inventory Data:

U.S. REGULATIONS:

SARA (311, 312) hazard class:

This product possesses the following SARA Hazard Categories:

Immediate Health (Acute): Delayed Health (Chronic):

Yes No

Flammability:

No

Pressure:

No

Reactivity:

No

RCRA Status

Not Regulated

STATE REGULATIONS (RTK):

California Proposition 65 Status:

No components are listed

Mineral Oil* - 8012-95-1

MARTK:

Present

NJRTK:

sn 2648

PARTK:

Present

INVENTORY STATUS:

United States TSCA - Sect. 8(b) Inventory:

This product complies with TSCA

Canada DSL Inventory List -

DSL Compliance has not been determined

EC No.

Compliance has not been determined

16. OTHER INFORMATION

Product name: QUAKERCUT™ 010 ES

Sources of key data used to compile the data sheet:

Material safety data sheets of the ingredients.

Reason for revision:

This data sheet contains changes from the previous version in section(s) 9

Prepared by:

Quaker Chemical Corporation -Safety, Health and Environmental Affairs Group - US

Page 6 of 7

SDS code: 014240-01 02

HMIS classification:	NFPA rating:
Health:	Health: 1
Flammability: 1	Flammability: 1
Reactivity:	Reactivity: 0
Personal Protection:	Special: NA

Personal protection recommendations should be reviewed by purchasers. Workplace conditions are important factors in specifying adequate protection.

Disclaimer

This product's safety information is provided to assist our customers in assessing compliance with safety/health/environmental regulations. The information contained herein is based on data available to us and is believed to be accurate. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or the hazards connected with the use of the product. Since the use of this product is within the exclusive control of the user, it is the user's obligation to determine the conditions for safe use of the product. Such conditions should comply with all regulations concerning the product. Quaker Chemical Corporation ("Quaker") assumes no liability for any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is attributable to the gross negligence of Quaker.

End of Safety Data Sheet

SDS code: 014240-01 02

^{*} Indicates possible chronic heath effect