KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004

PAGE NO. 1631.1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME W.M. BARR & COMPANY, INC. ADDRESS 2105 Channel Ave. Memphis, TN 38113

USA

EMERGENCY TELEPHONE #1

EMERGENCY CONTACT W.M. Barr Technical Services

EMERGENCY INFORMATION
"3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #

CHEMICAL FORMULA

PRODUCT NAME AC MINERAL SPIRITS 1 GL

REVISED BY W. M. Barr Technical Services

REVISION DATE

W.M. Barr Technical Services		-,			_	<b></b> -		
SECTION 2. COMPOSI	TION/INF	RMATION	ON INGREDIEN	TS				
				CARCINOGENICITY				
SUBSTANCE DESCRIPTION	PER	CENT	CAS#	NTP	ACGIH	OSHA	IARC	
		95-100	8052-41-3	N	N	N	N	
** ABOVE INGREDIENT CONSISTS STODDARD SOLVENT, TYPE III	OF THE F	OLLOWING 95-100	** 8052-41-3	N	N	N	N	x422745
SECTION 3. REGULATORY INFORMATION								
EXPOSURE LIMITS/REGULATORY INFORMATION								
SUBSTANCE DESCRIPTION	REG. AGCY	U/M	TWA	STE		CEIL	SKIN	PEL
MINERAL SPIRITS	ACGIH OSHA	PPM PPM	N/E N/E	N/!	Ē E	N/E N/E	N	N/E N/E
STODDARD SOLVENT, TYPE III	ACGIH OSHA	PPM PPM	100.00	N/	E E	N/E N/E	N N	500.00

ADDITIONAL REGULATORY INFO
The time weighted average (TWA) value described herein is a
threshold limit value (TLV) as established by ACGIH. The
permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)
Ingredients in this product are not listed on California's Prop 65
list: "Chemicals Known to the State to Cause Cancer or Reproductive
Toxicity."

SEC. 313 SUPPLIER NOTIFICATION The following information must be included in all MSDS that are copied and distributed for this material.

This product contains no chemicals subject to the reporting requirements of SARA III: Section 313.

### KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004

PACE NO. 1631.1

3. REGULATORY INFORMATION (CONTINUED) SECTION

CLEAN AIR ACT This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD
This document is prepared in accordance with the OSHA Hazard
Communication Standard (29 CFR 1910.1200). This MSDS contains
thirteen (13) sections.

INHALATION ACUTE EXPOSURE EFFECTS
May cause dizziness, headache, watering of eyes, eye irritation,
weakness, nausea, muscle twitches, and depression of central nervous
system. Severe overexposure may cause convulsions, unconsciousness, system. Sand death.

SKIN CONTACT ACUTE EXPOSURE EFFECTS None known.

EYE CONTACT ACUTE EXPOSURE EFFECTS May cause irritation.

INGESTION ACUTE EXPOSURE EFFECTS
Harmful or fatal if swallowed. May cause nausea, weakness, muscle twitches, gastrointestinal irritation, diarrhea, unconsciousness, convulsions, and death.

CHRONIC EXPOSURE EFFECTS
Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause skin irritation, anemia, bone marrow damage, liver damage, and jaundice.

MEDICAL CONDITIONS AGGRAVATED None known.

PRIMARY ROUTE OF EXPOSURE Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES

INHALATION
If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT Wash with soap and water.

EYE CONTACT Flush with large quantities of water for at least 15 minutes. If irritation from contact persists, get medical attention.

INGESTION
DO NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

KLEAN-STRIP GILLESPIE KWIK DUFFY'S MATERIAL SAFETY DATA SHEET

1/27/2004 herry DATE PRINTED:

RAGE NO. 1631,1

SECTION (continued)

TE TO PHYSICIAN
IS formula is registered with POISINDEX.
Il your local poison control center for further information.
SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE HMIS NFPA HEALTH 2 1 FLAMMABILITY 2 REACTIVITY oʻ OTHER a NA

FLASH METHOD

FLASH POINT 107.00 F

41.66 C

LOWER EXPLOSION LIMIT

GENERAL COMMENTS OSHA FLAMMABILITY: Class II

EXTINGUISHING METHOD
Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or contined areas. Storage containers exposed to fire should be kept gool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS
CAUTION! COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL
OTHER SOURCES OF IGNITION.

# SECTION 7. ACCIDENTAL RELEASE MEASURES

CLEAN-UP
Keep unnecessary people away; isolate hazard area and deny entry.
Stay upwind, out of low areas, and ventilate closed spaces before
entering. Shut off ignition sources; keep flares, smoking or flames
out of hazard area. SMALL SPILLS: take up liquid with sand, earth
or other noncombustible absorbent material and place in a plastic
container where applicable. LARGE SPILLS: dike far ahead of spill
for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL Dispose in accordance with applicable local, state and federal regulations.

## KLEAN-STRIP GILLESPIE KWIK DUFFY'S P&D MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004

MSDS NO. 1631,1

## SECTION 8. HANDLING AND STORAGE

STORAGE
Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING
Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION

# SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION PROTECTION
Use only with adequate ventilation to prevent build-up of vapors.
Open all windows and doors. Use only with a cross ventilation of
moving fresh air across the work area. If strong odor is noticed or
you experience slight dizziness, headache, nausea, or eye-watering STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against

SKIN PROTECTION
Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION
Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VOLATILE % 100.000 by weight

BOILING POINT GT 316.00 F

157.77 C BOILING RANGE: 316 F - 360 F

KLEAN-STRIP GILLESPIE MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004

PAGE NO. 1631.1

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VAPOR DENSITY (Air = 1.0) Heavier than air

EVAPORATION RATE Slower than ether

BULK DENSITY 6.380 lbs/gal at 75 F

ph factor N/E

PHOTOCHEMICALLY REACTIVE

MAX V.O.C. 815 grams per liter (excluding exempt solvents & water)

MAX VAPOR PRESSURE (of the V.O.C.) 2mm Hg at 20 degrees C

SECTION 12. STABILITY AND REACTIVITY

INCOMPATIBILITIES
Incompatible with strong oxidizing agents.

DECOMPOSITION Decomposition may produce carbon monoxide and carbon dioxide.

POLYMERIZATION Will not occur

SECTION 13. ADDITIONAL INFORMATION

IMPORTANT NOTE
The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

LEGEND:

PPM = parts per million

MG/M3 = milligrams per cubic meter

N/E or NE = none established

GT = greater than

N/A or NA = not applicable

TCC = tag closed cup

TCC = tag open cup

PMCC = tag open cup

PMCC = Pensky-Martens closed cup

IDLH = Immediately Dangerous to Life and Health

\*\*\*END OF MSDS\*\*\*