





# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name:

545 Thread Sealant Pneumatic/Hydraulic Fittings

Product type: Anaerobic Sealant

Company address: Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067 Item No. :

54531 United States

Region: Unite Contact Information:

Telephone: 860.571.5100 Emergency telephone: 860.571.5100

Internet: www.loctite.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Polyglycol dioctanoate 18268-70-7	<u>%</u> 30-60	ACGIH TLV None	OSHA PEL None	OTHER None
Polyglycol dimethacrylate 25852-47-5	10-30	None	None	None
Hydroxyaikyl methacrylate 868-77-9	10-30	None	None	3 ppm (ceiling)
Silica, amorphous, fumed, crystalline-free 112945-52-5	1-5	6 mg/m³ TWA	10 mg/m³ TWA	3 mg/m³ TWA respirable dust
Cumene hydroperoxide 80-15-9	1-5	None	None	1 ppm (6 mg/m³) Skin (WEEL)
1-Acetyl-2-phenylhydrazine 114-83-0	0.1-1	None	None	None

# 3. HAZAROS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state: Liquid Color: Purple Odor: Mild

HEALTH:
FLAMMABILITY:
PHYSICAL HAZARD:
Personal Protection:

2\* 1 1 See Section 8

WARNING:

CAUSES EYE AND SKIN IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Skin contact: Eye contact: May cause respiratory tract irritation.

Moderate skin irritation. May cause allergic skin reaction.

Contact with eyes will cause irritation.

Ingestion: May be harmful if swallowed.

Item No.: 54531

Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings

Existing conditions aggravated by exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

# 4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

### 5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

# 7 FANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling.

Storage: For safe storage, store at or below 38°C (100°F). Keep in a cool, well ventilated area away from heat,

sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### & EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be required if concentrations

exceed occupational exposure limts.

Item No.: 54531 Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves. Glove recommendations are based upon

permeation study results for similar products.

Eye/face protection:

Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid

Color: Odor: Purple Mild

Vapor pressure:

Less than 5 mm Hg at 27°C (80°F)

pH:

Not applicable

Boiling point/range:

Greater than 149°C (300°F)

Melting point/range:

Not available

Specific gravity:

1.02

Vapor density: Evaporation rate: Not available

Solubility in water:

Slight

Partition coefficient (n-octanol/water):

Not available

VOC content:

1.9912%; 19.0069 grams/liter

### 10: STABILITY AND REACTIVITY

Stability:

Stable.

Hazardous polymerization:

Will not occur.

Hazardous decomposition products:

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Phenols. Irritating organic vapors.

Incompatability:

Strong oxidizers. Reducing agents. Acids. Bases. Rust. Zinc. Aluminum. Iron. Copper. Alkalis.

Aldehydes. Amines. Free radical initiators. Peroxides.

Conditions to avoid:

Exposure to sunlight. Heat, flames and sparks. See "Handling and Storage" (Section 7) and

"Incompatability" (Section 10).

#### 11 TUXICOLOGICAL INFORMATION

Product toxicity data:

Acute oral LD50 greater than 5000mg/kg (rat)(estimated). Acute demail LD50 greater than 2000 mg/kg

(rabbit) (estimated).

#### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dioctanoate 18268-70-7	No	No	No
Polyglycol dimethacrylate 25852-47-5	No	No	No
Hydroxyalkyl methacrylate 868-77-9	No	No	No
Silica, amorphous, fumed, crystalline-free 112945-52-5	No	No	No
Cumene hydroperoxide 80-15-9	No	No	No
1-Acetyl-2-phenylhydrazine 114-83-0	No	No	No

#### Literature Referenced Target Organ & Other Health Effects

Item No. :

54531

Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings

3 of 5

Hazardous components	Health Effects/Target Organs	
Polyglycol dioctanoate 18268-70-7	Irritant	
Polyglycol dimethacrylate 25852-47-5	Allergen, Irritant	
Hydroxyalkyl methacrylate 868-77-9	Allergen, Irritant	
Silica, amorphous, fumed, crystalline-free 112945-52-5	Nuisance dust	
Cumene hydroperoxide 80-15-9	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	
1-Acetyl-2-phenylhydrazine 114-83-0	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity	

#### 12. EGOLOGICAL INFORMATION

**Ecological information:** 

Not available

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number:

Not a RCRA hazardous waste.

## A TRANSPORT INFORMATION

#### U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:

Unrestricted

Hazard class or division:

None None

Identification number: Packing group:

None

# International Air Transportation (ICAO/IATA):

Proper shipping name:

Unrestricted

Hazard class or division:

None

Identification number:

None

Packing group:

None

# WaterTransportation (IMO/IMDG):

Proper shipping name:

Unrestricted

Hazard class or division:

None

Identification number:

None

Packing group:

None

Marine pollutant:

None

Item No.:

54531

### United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

4-Methoxyphenol (150-76-5).

CERCLA/SARA Section 302 EHS:

None above reporting de minimus.

CERCLA/SARA Section 311/312:

Immediate Health Hazard, Delayed Health Hazard

CERCLA/SARA 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene

hydroperoxide (CAS# 80-15-9) .

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

#### Canada Regulatory Information

CEPA DSL/NDSL Status: WHMIS hazard class:

Contains one or more components listed on the Non-Domestic Substances list.

# #16, OTHER INFORMATION #

This material safety data sheet contains changes from the previous version in sections: 9

Prepared by:

Kyra Kozak Woods, Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically discialms all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Item No.: 54531 Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings