



Revision Date: 02/09/2006

Issue date: 02/09/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Heavy Duty Anti-Seize Metal-Free Lubricant	Item No. : 51606
Product type: Lubricant	Region: United States
Company address: Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067	Contact Information: Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Lubricant base oil UNKNOWN	30-60	None	None	None
Calcium fluoride 7789-75-5	10-30	2.5 mg/m ³ TWA as F	2.5 mg/m ³ TWA as F	None
Graphite 7782-42-5	10-30	2 mg/m ³ TWA respirable fraction, all forms except graphite fibers	15 mg/m ³ (total), 5 mg/m ³ (respirable)	None
Calcium sulfonate complex thickener UNKNOWN	10-30	None	None	None
Calcium stearate 1592-23-0	5-10	10 mg/m ³ TWA	None	None
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	5-10	5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist)	5 mg/m ³ TWA (mist)	None
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	5-10	5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist)	5 mg/m ³ TWA (mist)	None
Benzenesulfonic acid, dodecyl, calcium salt 26264-06-2	1-5	None	None	None

3. HAZARDS IDENTIFICATION

<u>EMERGENCY OVERVIEW</u>		
<u>HMIS:</u>		
Physical state: Paste	HEALTH:	1
Color: Brown	FLAMMABILITY:	1
Odor: Mild petroleum	PHYSICAL HAZARD:	0
	Personal Protection:	See Section 8
CAUTION: MAY CAUSE EYE AND SKIN IRRITATION.		

Relevant routes of exposure: Skin, Eyes

Potential Health Effects

Item No. : 51606

Product name: Heavy Duty Anti-Seize Metal-Free Lubricant

Inhalation: May cause respiratory tract irritation. This product has low volatility and is not expected to cause respiratory tract irritation during normal conditions of use.
Skin contact: Prolonged or repeated contact may cause irritation.
Eye contact: Contact with eyes will cause irritation.
Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.
Skin contact: Wash with soap and water. Get medical attention if symptoms develop and persist.
Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion: Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F)
Autoignition temperature: Not determined
Flammable/Explosive limits-lower %: Not determined
Flammable/Explosive limits-upper %: Not determined
Extinguishing media: Carbon dioxide (CO2). Dry chemical. Foam. Water spray.
Special fire fighting procedures: None
Unusual fire or explosion hazards: None
Hazardous combustion products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Do not allow material to contaminate ground water system.
Clean-up methods: Scrape up as much material as possible. Clean residue with soap and water. Dispose of in accordance with local and national regulations.

7. HANDLING AND STORAGE

Handling: Keep container closed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage: Keep in a cool, well ventilated area.
Incompatible products: Oxidizing agents.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

Item No. : 51606

Product name: Heavy Duty Anti-Seize Metal-Free Lubricant

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Ensure adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respiratory use (29 CFR 1910.134).
Skin protection:	Cover as much of the exposed skin area as possible with appropriate clothing.
Eye/face protection:	Safety glasses with side-shields. Goggles.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Brown
Odor:	Mild petroleum
Vapor pressure:	Not determined
pH:	Not applicable
Boiling point/range:	288°C (550°F)
Melting point/range:	Not available
Specific gravity:	1.17999
Vapor density:	Heavier than air
Evaporation rate:	Not determined
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	Essentially Zero (Exempt Compounds)

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Hydrocarbons.
Incompatibility:	Oxidizing agents.
Conditions to avoid:	None known.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Lubricant base oil UNKNOWN	No	No	No
Calcium fluoride 7789-75-5	No	No	No
Graphite 7782-42-5	No	No	No
Calcium sulfonate complex thickener UNKNOWN	No	No	No
Calcium stearate 1592-23-0	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	No	No	No
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	No	No	No
Benzenesulfonic acid, dodecyl, calcium salt 26264-06-2	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Lubricant base oil UNKNOWN	No data
Calcium fluoride 7789-75-5	Muscle, Respiratory, Teeth
Graphite 7782-42-5	Lung
Calcium sulfonate complex thickener UNKNOWN	No data
Calcium stearate 1592-23-0	No Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	Irritant
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	Irritant
Benzenesulfonic acid, dodecyl, calcium salt 26264-06-2	Eyes, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Not regulated

Item No. : 51606

Product name: Heavy Duty Anti-Seize Metal-Free Lubricant

Hazard class or division: None
Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: Immediate Health Hazard
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). None.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2,15

Prepared by: C.J. Michaels, Senior Product Safety & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.