

MAY 14 '07 10:01 FR

22

6178843539 TO 13169437116

P.02/03

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

RMS \$1400
4310

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
ONS No. 1218-0072



IDENTITY (As Used on Label and List)
Easy-Sweep Vinyl Matting

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name
The Biltrite Corporation
Address (Number, Street, City, State, and ZIP Code)
P.O. Box 9045
51 Sawyer Road
Waltham, MA 02454-9045

Emergency Telephone Number
Telephone Number for Information
800-877-8775
Date Prepared 05/24/04
Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Easy-Sweep Vinyl Matting products are classified as "ARTICLES" under applicable EPA Regulations and OSHA Standards. Under normal conditions of use, these products do not release or otherwise result in exposure to a hazardous chemical.				

Section III - Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	1.40-1.80
Vapor Pressure (mm Hg)	N/A	Melting Point	8250°F - 300°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water			
Appearance and Odor			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	N/A	LEL	UEL
Extinguishing Media	Water - CO2				
Special Fire Fighting Procedures	Standard procedures with self-contained air breathing apparatus.				
Unusual Fire and Explosion Hazards	None.				

MAY 14 '07 10:02 FR

22

6178843539 TO 13169437116

P.03/03

Section V -- Reactivity Data

Stability	Unstable	Conditions to Avoid
	Stable	

Incompatibility (Materials to Avoid) Direct exposure to flame.

Hazardous Decomposition or Byproducts Hydrogen chloride gas generated @120 - 150°C.

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	

Section VI -- Health Hazard Data

Route(s) of Entry: Ingestion? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: NTP? IARC Monographs? OSHA Registered?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure

N/A

Emergency and First Aid Procedures

N/A

Section VII -- Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

N/A

Waste Disposal Method In accordance with Local, State and Federal Regulations.

Precautions to be Taken in Handling and Storing

N/A

Other Precautions

N/A

Section VIII -- Control Measures

Respiratory Protection (Specify Type)

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other
	Only if dust is generated.	N/A
	In keeping with good Plant practices.	N/A

Protective Gloves None required. Eye Protection In keeping with good safety practices.

Other Protective Clothing or Equipment None required.

Work Hygienic Practices

N/A